

WLA Precision



- R410a Refrigerant Circuit
- Aluminum Finned Copper Tube Condenser
- Stainless Steel Plate Evaporator
- Thermostatic Expansion Valve
- Non Ferrous Water Circuit
- Pump and Tank Onboard
- Adjustable bypass with manometer
- Axial Fans
- Electrical Level Indicator
- General Alarm Signals



WLA Precision R410A



CODICE - CODE - ARTIKELNUMMER - CÒDIGO	M.U.	WLAJo	WLALo	WLAM7
Capacità di raffreddamento (°) - Cooling capacity (°) - Kühlleistung (°) - Potencia frigorífica (°)	W	96000	112000	130000
Potenza elettrica assorbita (") - Absorbed power ca. (") - Leistungsaufnahme (") - Potencia absorbida (")	W	25200	28400	33000
SEPR		4.74	4.72	4.93
Gas refrigerante - Refrigerant gas - Kältemittel - Gas refrigerante		R410A	R410A	R410A
Carica gas refrigerante - Charge refrigerant gas - Kältemittelfüllung - Carga de refrigerante	kg	12,5 + 12,5	13,0 + 13,0	12,0 + 12,0
Circuiti frigo/Compressori-Cooling circuits/Compressors Schaltungen - Kühlschrank/Kompressoren- Circuitos/Compresores	N°	2 / 4	2 / 4	2 / 4
Alimentazioni - Power supplies - Spannungversorgungen - Tensiones de alimentación	V-Hz	400-3-50 460-3-60	400-3-50 460-3-60	400-3-50 460-3-60
Alimentazione secondaria - Auxiliaries feed - Steuerungsspannung - Alimentación secundaria	VAC	24	24	24
Allacciamento - Connections - Elektrische Anschlüsse - Conexiones eléctricas		Morsettiera / Terminal / Klemmen / Terminales		
Tipo di ventilatore/N° - Fan type/N° - Lüfter/N° - Tipo de ventilador/N°		Assiale/1 - Axial/1		
Portata aria a bocca libera - Condenser fan air flow (free) - Luftförderleistung freiblasend - Flujo aire ventilador de condensador	m³/h	2 x 24000	2 x 24000	2 x 24000
Potenza totale assorbita ventilatore - Total fan absorbed power - Elektrische Leistungsaufnahme Lüfter - Potencia absorbida de ventilador	W	2 x 2100	2 x 2100	2 x 2100
Potenza assorbita pompa- Pump absorbed power - Elektrische Leistungsaufnahme Pumpe - Potencia absorbida bomba	kW	2470	2470	2470
Portata nominale - Nominal flow - Nom. Durchfluss - Caudal nominal	l/min	270	320	370
Prevalenza disponibile nom (Med Prex)- Available head nom (Med Prex)- Externe Förderhöhe nom (Med Prex)- Presión nom (Med Prex)	bar	2.2 (5)	2 (4,5)	1.8 (5,2)
Capacità della vasca - Tank capacity - Tankinhalt - Capacidad del depósito	l	300	300	300
Attacchi idraulici - Hydraulic connections - Wasseranschlüsse - Conexiones hidráulicas	Ø	2"	2"	2"
Rumorosità ("") - Noise level ("") - Geräuschpegel ("") - Nivel de ruido ("")	dB(A)	74	74	74
Altezza x Larghezza x Profondità - Height x Width x Depth Höhe x Breite x Tiefe - Altura x Anchura x Profundidad	mm	2300 x 1160 x 2462	2300 x 1160 x 2462	2300 x 1160 x 2462
Peso a vuoto - Shipping weight - Gewicht - Peso	kg	950	1100	1200

Your trusted temperature & humidity control **partners**
Sales Service Rental