

WPA Techno



- R410a Refrigerant Circuit
- Aluminum Microchannel Condenser
- Shell and Tube Evaporator
- Electronic Expansion Valve
- Axial Fans
- Pump and Tank on board (option)
- Electrical Level Indicator
- General Alarm Signals



WPA Standard

CODICE - CODE - ARTIKELNUMMER - C�DIGO		M.U.	WPA060	WPA070	WPA080	WPA090	WPA100	WPA110
Capacit� di raffreddamento - Cooling capacity - K�hlleistung - Potencia frigor�fica	W15L32	kW	210,5	237,7	298,3	314,2	343	416,3
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W15L32	kW	51,8	63,2	71,6	82	91,7	99,7
SEPR			5,36	5,36	5,02	5,72	5,68	5,88
Capacit� di raffreddamento - Cooling capacity - K�hlleistung - Potencia frigor�fica	W7L35	kW	165,5	187,5	222,6	245,2	266,5	318,6
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W7L35	kW	53,2	64,4	73,7	83	91,6	100,4
Gas refrigerante - Refrigerant gas - K�ltemittel - Gas refrigerante			R410A	R410A	R410A	R410A	R410A	R410A
Carica gas refrigerante - Charge refrigerant gas - K�ltemittelf�llung - Carga de refrigerante		kg	18	17,5	17	18	15,5	22,5
Circuiti frigo/Compressori - Cooling circuits/Compressors - Schaltungen - K�hlschrank/Kompressoren - Circuitos/Compresores		N�	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4	2 / 4
Tensione nominale - Rated voltage - Nennspannung - Tensi� nominal		V~	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal		Hz	50 60	50 60	50 60	50 60	50 60	50 60
Altezza x Larghezza x Profondit� - Height x Width x Depth - H�he x Breite x Tiefe - Altura x Anchura x Profundidad		mm	2410x3100x2206	2410x3100x2206	2410x3100x2206	2410x3100x2206	2410x3100x2206	2410x4400x2206
Peso a vuoto - Shipping weight - Gewicht - Peso		kg	2293	2323	2395	2420	2440	3119

CODICE - CODE - ARTIKELNUMMER - C�DIGO	M.U.	WPA120	WPA140	WPA160	WPA180	WPA200	
Capacit� di raffreddamento - Cooling capacity - K�hlleistung - Potencia frigor�fica	W15L32	kW	460,3	499,9	564,9	657,3	727,4
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W15L32	kW	114,1	129,5	132,1	174,1	200,6
SEPR			5,62	5,87	5,84	5,79	6,18
Capacit� di raffreddamento - Cooling capacity - K�hlleistung - Potencia frigor�fica	W7L35	kW	353,1	385,1	432	504	559,3
Potenza elettrica assorbita - Absorbed power ca. - Leistungsaufnahme - Potencia absorbida	W7L35	kW	114,2	127,5	131,9	173,6	199,8
Gas refrigerante - Refrigerant gas - K�ltemittel - Gas refrigerante		R410A	R410A	R410A	R410A	R410A	
Carica gas refrigerante - Charge refrigerant gas - K�ltemittelf�llung - Carga de refrigerante	kg	25	24,5	69	80,5	89	
Circuiti frigo/Compressori - Cooling circuits/Compressors - Schaltungen - K�hlschrank/Kompressoren - Circuitos/Compresores	N�	2 / 4	2 / 4	2 / 4	2 / 6	2 / 6	
Tensione nominale - Rated voltage - Nennspannung - Tensi� nominal	V~	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3	400 . 3 460, 3	
Frequenza nominale - Nominal frequency - Nennfrequenz - Frecuencia nominal	Hz	50 60	50 60	50 60	50 60	50 60	
Altezza x Larghezza x Profondit� - Height x Width x Depth - H�he x Breite x Tiefe - Altura x Anchura x Profundidad	mm	2410x4400x2206	2410x4400x2206	2410x5770x2206	2410x5770x2206	2410x5770x2206	
Peso a vuoto - Shipping weight - Gewicht - Peso	kg	3173	3219	4158	4559	4561	

Your trusted temperature & humidity control partners
Sales Service Rental