

NR-15 Hire Chiller

Product Overview

Robust design - Specifically designed for demanding process cooling applications

Ecodesign compliant - all models fully comply with ErP2021 -SEPR HT (EU) 2016/2281 - SEPR MT (EU) 2015/1095

Wide operating range – operates in ambient temperatures from +45°C down to -10°C with cooling fluid supply temperatures between +30°C and -10°C

Pressurised hydraulic circuit - equipped with stainless steel brazed plate evaporator c/w differential pressure switch, integral storage tank c/w level indicator, drain/overflow connections, level switch & integral pressure relief

Integral circulation pump - nominal 3 bar discharge pressure

Isolation valves & strainers - fitted to fluid connections



Nominal Cooling Capacity (1)	14.0 kW
Nominal Power Consumption (1)	3.7 kW
EER (1)	3.78 kW/kW

Operating Limits

Minimum/Maximum Cooling Fluid Flow Rate20/70 I/min

Electrical Data

Power Supply	400/3/50 V/ph/Hz
Power Connections	16A 5 pin plug
IP Rating	IP54

Cooling Circuit

Refrigerant / Compressor Type	R410A/Scroll
Number of Compressors / Circuits / Fans	1/1/1

Hydraulic Circuit

Nominal Cooling Fluid Flow Rate (1)	40 l/min
Nominal Pump Discharge Pressure (1)	3.49 bar
Connections	1" Camlock
Internal Volume	100 litres

Physical Data

Length (2)	1,580 mm
Width (2)	
Height (2)	
Operating Weight (2)	
Sound Pressure Level (2)	



(1) Performance data based on operating conditions of +7°C cooling fluid outlet temperature / +12°C cooling fluid inlet temperature / +30°C ambient temperature

(2) Dimensions / weights include crash frame

(3) Sound pressure at 10m average value obtained in a free field on a reflecting plane at a distance of 10m from the unit according to EN ISO 9614-2 - tolerance +/- 2 dB

Still have a question?

Get in touch with one of our expert team today.



01422 371711




sales@newsome.ltd.uk



www.newsome.ltd.uk







Cooling Fluid Outlet Temperature (°C)

The level of performance provided by each machine depends on the conditions at which it is operating. The two factors determining performance are ambient air temperature and the required cooling fluid outlet temperature. The above graphs illustrate the cooling capacity and nominal running current – at three different operating ambient temperatures - based on differing cooling fluid outlet temperatures.



20°C

25°C



