

NR-H300G Gas Boiler

NR-H300DF

Product Overview

- Compact** – very small footprint provides site flexibility
- Weatherproof** – installed within a steel frame suitable for external siting
- Added redundancy** – consists of 2 x 150 kW gas fired boilers to provide extra peace of mind
- Fully packaged** – complete with all necessary safety valves/switches along with flexible connections to ease installation
- Suitable for single phase supply** – large heating capacity is achieved from a relatively small electrical load
- Wide range of ancillaries available** – fuel tanks, fuel lines, calorifiers, hoses & cables can all be supplied to provide a complete solution



Performance Data

Nominal Heating Capacity.....300 kW
Nominal Fuel Consumption – Gas34 m³/hr

Operating Limits

Minimum/Maximum Heating Fluid Supply Temperature 50/90 °C
Maximum Working Pressure10.0 bar

Electrical Data

Power Supply230/1/50 V/ph/Hz
Power Connection16 A 3 Pin Plug

Hydraulic Circuit

Nominal Heating Fluid Flow Rate18 m³/hr
Connections 50 mm

Physical Data

Length2,200 mm
Width800 mm
Height1,800 mm
Operating Weight.....1,100 kg

Still have a question?

Get in touch with one of our expert team today.

- ☎ 01422 371711
- ✉ sales@newsome.ltd.uk
- 🌐 www.newsome.ltd.uk

