

NR-IDF100 Indirect Diesel Fired Heater

NR-IDF100

Product Overview

Versatile – robust mobile indirect diesel fired heater suitable for a wide range of different applications

Dual voltage capability – can operate on either 110 / 230 volt power supplies via selector switch

High efficiency – integral heat exchanger achieves 92% efficiency

Robust Design – complete with durable body panels, large wheels & forklift slots

Digital Thermostat – manages the fan, the burner & provides overheat protection



Performance Data

Nominal Heating Capacity 110 kW
 Nominal Air Flow Rate 8,000 m³ /hr
 Nominal Fuel Consumption 10.9 l/hr
 Maximum Ventilation Back Pressure 300 Pa

Electrical Data

Power Supply – Dual Voltage 110-230/1/50 V/ph/Hz
 Power Connections 110V Supply 32 A
 Power Connection – 230V Supply 16 A

Heating Circuit

Spigot Connections 500 mm Ø
 Maximum Discharge Duct Length 18 m
 Flue Connection Size 200 mm
 Flue Height 1 m

Physical Data

Length 2,230 mm
 Width 780 mm
 Height 1,340 mm
 Operating Weight 350 kg

Still have a question?

Get in touch with one of our expert team today.

☎ 01422 371711
 ✉ sales@newsome.ltd.uk
 🌐 www.newsome.ltd.uk

