

# NR-LTFC25 Low Temperature Fan Coil

NR-LTFC25

## Product Overview

**Robust design** – industrial in-room unit designed for use within various cold storage applications

**Integrated defrost heating** – allowing programmable automatic defrost cycles for both the heat transfer coil & condensate tray

**Wide operating range** – capable of supplying air at temperatures as low as -20°C

**Energy efficient** – equipped with the latest EC fans allowing fan speed to be constantly regulated

**Unique wi-fi control** – allows for adjustment without the user needing to enter the cold storage area served



## Performance Data

Nominal Cooling Capacity (1) .....25 kW  
Nominal Air Flow Rate.....15,200 m³/hr

### Operating Limits

Minimum/Maximum Air Outlet Temperatures ..... -20/+60 °C  
Maximum Working Pressure .....10 bar

### Electrical Data

Power Supply .....400/3/50 V/ph/Hz  
Power Connections .....16 A 5 Pin Plug  
IP Rating.....IP55

### Hydraulic Circuit

Nominal Cooling Fluid Flow Rate (1).....6.19 m³/hr  
Internal Volume.....54 Litres  
Connections .....DN40 Flanged  
Condensate Drain Connection.....1" BSP

### Defrost Heaters

Heater Capacity .....7.50 kW

### Physical Data

Length .....2,700 mm  
Width .....1,120 mm  
Height .....1,440 mm  
Operating Weight.....451 kg  
Sound Pressure level (2).....53.4 dB(A)


(1) Performance data based on operating conditions of -8°C cooling fluid inlet temperature / -4°C cooling fluid outlet temperature / +4°C air inlet temperature / 15,200 m³/hr nominal air flow rate

(2) Noise level based on LpA at a distance of 3 meters and in accordance with BS EN:13487 Parallel Pipe. This does not allow for any fluctuations based on the integration and operation with other equipment, and should be considered a guide only.

## Still have a question?


Get in touch with one of our expert team today.

☎ 01422 371711  
✉ sales@newsome.ltd.uk  
🌐 www.newsome.ltd.uk



# NR-LTFC25 Low Temperature Fan Coil

## Cooling Capacity



The level of performance provided by each machine depends on the conditions at which it is operating. The two factors determining performance are ambient air temperature and the required cooling fluid outlet temperature. The above graph illustrates the cooling capacity achieved at three different sets of cooling fluid temperatures – based on differing ambient temperatures.

