

NR-PAC P9 Portable Cooler

NR-PAC P9

Product Overview

Eco-friendly – portable monblock units comprising the latest technology which utilises low GWP R454C refrigerant

High efficiency – backward curved fan impellers coupled with variable speed EC motors

Digital thermostatic control – possible for the user to set a desired set point using the integrated controller

Twin discharge ducts – allowing for cooling of two separate areas simultaneously

Exhaust duct – can be ducted up to 10m away allowing units to be sited away from warm exhaust point



Performance Data

Nominal Cooling Capacity (1)8.3 kW
Nominal Air FlowRate.....1080 m³/hr
Typical Cooled Area.....220 m²

Operating Limits

Minimum/Maximum Cooling Fluid Flow Rate 15/35 °C

Electrical Data

Power Supply230/1/50 V/ph/Hz
Power Connections13A 3 pin plug
IP Rating IP2X

Cooling Circuit

Refrigerant R454C
Exhaust Duct (Max. length 10m).....200 mmØ
Discharge Ducts (Max. length 1.25m).....2 x 150 mmØ

Physical Data

Length (2)774 mm
Width (2)526 mm
Height (2)1,192 mm
Operating Weight (2)95 kg

Still have a question?

Get in touch with one of our expert team today.

☎ 01422 371711
✉ sales@newsome.ltd.uk
🌐 www.newsome.ltd.uk

